

Always read entire label before using product



- FEATURES:**
- High resistance to acids and salts
 - Resists wash off
 - Provides long lasting lubrication and corrosion protection
 - Penetrates to the core of the rope
 - Compatible with most coating systems

CONTENTS: Lanolin (a natural product), blended with an evaporative carrier to enable ease of application and enhance penetration

USAGE EXAMPLES:

- Suitable for all wire ropes above 16mm or any wire ropes operating in corrosive environments
- Ideal for rig and marine cranes, or any wire ropes working in the splash zone
- Ideal for use around waterways and coastal environments
- Lubrication of ropes in environmentally sensitive areas where salt water is an issue
- Ideal for use on industrial high load bearing chains

STORAGE & TRANSPORT:

- This product is classified as non-Dangerous Goods
- Store in a cool, dry place
- Shelf life - virtually indefinite if kept sealed in reasonable conditions



PREPARATION:

- Inspect wire rope for damage.
- Clean wire rope if practical for best results using wire brush or high pressure water to remove foreign debris.
- Lanotec Wire Rope Lube is compatible with all oil based manufacturers lubricants.

APPLICATION:

- Shake container to ensure product is mixed correctly. Colder climates will require extra agitation.
- Lanotec Wire Rope Lube is sprayable when above 25°C, or can also be hand applied or brushed on at any temperature.
- Place catching container under lube zone to collect any spills or overflow.
- Apply enough Lanotec Wire Rope Lube to fill the valley of the wire rope only.
- Can be sprayed or dipped.

REAPPLICATION:

- With wire ropes over 16mm a quarterly visual inspection is recommended. Lanotec Wire Rope Lube should be reapplied at this time.
- Because Lanotec Wire Rope Lube is a long lasting high performance product, it can be reapplied during your normal wire rope lubrication service intervals.